



BPChem

PRODUCT	DESCRIPTION	USES	DOSAGE/ CONSUMPTION/ COVERAGE/ YIELD	PACKING
BPChem ZINC PR	Two component zinc rich epoxy based anti-corrosive primer to provide galvanic protection to the rebar.	Zinc rich primer is the recommended anti-corrosive primer for partially exposed reinforcement and structural steel embedded in concrete.	8.0 m ² /Litre / Coat	3.2 Kg Combo Pack
BPChem RENDERCE M FC	Single component, polymer modified cementitious honeycombs and pinhole filler.	For application to minor imperfections in concrete and masonry surface upto 5mm.	6.0m ² @3mm Thickness	25 Kg Bags
BPChem MICROCRETE	Single component high strength free flow non-shrink micro-concrete for precision structural and concrete patch repairs.	Used for conventional repair of honeycombed concrete and to fill recesses of broken structure of concrete. Make use of its non shrink and excellent bonding properties to repair soffit of beams, slabs and RCC column jacketing.	9 Itrs/ 20 kg bag	20 Kg Bags
BPChem RENDERCE M GP	Single component, general purpose shrinkage controlled, polymer modified, cementitious patch repair mortar system.	General purpose polymer modified repair mortar for vertical and overhead patch repairs of concrete and masonry elements. Rendering of honey combed concrete. For doing patch repairs by hand or trowel application, where form work cannot be erected.	1.85 kg / m ² / mm	25 Kg HDPE Bags
BPChem CRACKFILL GP	Ready to use filler for masonry and plaster cracks in pasty form with excellent weather durability and flexibility.	Internal and external plastered brick masonry wall cracks upto 5 mm width.	25-30 running meter/kg (for crack size 5 mm width and 5 mm depth)>/ mm	500 gm & 1 kg

PRODUCT	DESCRIPTION	USES	DOSAGE/ CONSUMPTION/ COVERAGE/ YIELD	PACKING
BPChem RENDERCEM 2K	2 pack thixotropic, polymer modified cementitious patching and adhesive mortar.	Used for thin layer applications to seal surface cracks upto 5 mm, blow holes, honeycombs to give a smooth level finish.	2.15 kg / sqm / 1 mm Thickness	25Kg + 8Kg Combo Pack
BPChem INSTA PLUG	Rapid setting cement based waterleak plugging mortar	For the rapid temporary patching and plugging of concrete segments, concrete and brick tunnel linings, sewage systems, below ground access chambers, pipes, basements, foundations and mines.	Yield: 0.55 Itrs / kg	1,5 & 25 kg Bags
BPChem POLYCRETE EP	Epoxy resin based patch repair mortar. Both clear and pigmented versions are available.	For lining ETP, STP and chemical tanks, cavity or pot hole repairs on factory floors, garages, repairing dams, (pointing) spillways, etc. where abrasion resistance is required alongwith high strength.	2m ² @ 5mm Thickness / Pack	20 kg Combo Pack
BPChem GROUT LVEP	Epoxy resin based 2-component high strength injection grout for very small gaps between 0.2- 10 mm. Moisture insensitive epoxy injection grout also available.	For injecting into cracks, honeycombs and cavities in concrete structures. It can also be used for grouting base plates with very narrow gaps having deep penetration and dynamic load resistance. It has good chemical resistant properties and bonding strength to most contact surfaces.	Yield: 0.95 Itr/ kg	1,3 Kg Tin Containers
BPChem POLYGROUT 1K	Flexible polyurethane injection foam for inhibiting continuous water infiltration.	To stop high water intrusion into cracks, joints and cavities in concrete underground structures, masonry or natural stone structures with deep penetration owing to its low viscosity.	Depends on the concrete porosity.	20 Itr Drums

PRODUCT	DESCRIPTION	USES	DOSAGE/ CONSUMPTION/ COVERAGE/ YIELD	PACKING
BPChem POLYGROUT 2K	Elastic polyurethane injection resin for permanent watertight sealing.	To permanently seal dry, damp or waterbearing and joints in concrete, masonry or natural stone structures. Remains flexible and can absorb limited movement.	Depends on the concrete porosity.	20.6 Itr Combo Pack
BPChem POLYCRETE SBR	Multipurpose SBR latex for waterproofing & structural repair system by using as mortar modifier.	Bathroom and Toilet waterproofing, repair mortar, injection grouting, bonding agent, corrosion protection of steel, heavy duty floor topping, polymer modified concrete.	5-7 kg POLYCRETE for 50 kg cement when used as a polymer modified repair mortar.	500 gm, 1,5, 20, 50, 200 Kg
BPChem DEMOLEX	Non-explosive expansion demolition grout.	It is designed for demolition of concrete, rocks, boulders and quarrying of natural stones that will be accomplished smoothly and efficiently. And the sensitive areas where vibration must be minimized.	Refer the Product Data sheet	10 Kg Bag
BPChem KLEEN RR	Rust remover, cleaning and etching agent.	It is used as a rust remover from steel bars prior to encasing in concrete/micro concrete. It can also be used on other steel surfaces prior to coating with epoxy systems.	2.0 - 2.5m ² /ltr approximately	1,5, 20 Ltrs

Follow us on:



info@bpchem.net
info@bptonline.in



+91 99807 89618